



**Part Number :** [762910068](#)  
**Product Description :** EdgeLine CoPlanar  
Connector, 6 Gbps, 0.75mm Pitch, 1.57mm PCB  
Thickness, 68 Circuits  
**Series Number :** 76291  
**Status :** Active  
**Product Category :** Card Edge Connectors



## Documents & Resources

### Drawings


- [762910068 sd.pdf](#)
- [PK-76291-001-001.pdf](#)
- [SP-76291-0002-001.zip](#)

### Specifications

- [AS-76291-001-001.pdf](#)
- [AS-76291-002-001.pdf](#)
- [PS-76291-001-001.pdf](#)

## Product Environment Compliance

### Compliance

GADSL/IMDS	Compliant with Exemption 44; 34; 33
China RoHS	 per SJ/T 11365-2006
EU ELV	Not Relevant
Low-Halogen Status	Low-Halogen per IEC 61249-2-21
REACH SVHC	Not Contained per D(2025)4165-DC (25 June 2025)
EU RoHS	Compliant per EU 2015/863

### Compliance Statements

- EU RoHS
- REACH SVHC
- Low-Halogen

## Industry Documents

- IPC 1752A Class C
- IPC 1752A Class D
- Molex Product Compliance Declaration
- IEC-62474
- chemSHERPA (xml)

## Substances of Interest

- PFAS

## EU RoHS Certificate of Compliance

## Additional Product Compliance Information

---

## Part Details

### General

Status	Active
Category	Card Edge Connectors
Series	76291
Description	EdgeLine CoPlanar Connector, 6 Gbps, 0.75mm Pitch, 1.57mm PCB Thickness, 68 Circuits
Component Type	Edgecard to PCB
Product Name	EdgeLine
UPC	883906112745

### Electrical

Current - Maximum per Contact	1.5A
Data Rate	5.0-12.0 Gbps
High Power Bay (30.0A or more)	No
Voltage - Maximum	50V AC (RMS)/DC

### Physical

Circuits (Loaded)	68
Circuits (maximum)	68
Color - Resin	Black
Durability (mating cycles max)	200
Edge Card Thickness	1.57mm
Entry Angle	N/A

Keying to Mating Part	N/A
Material - Metal	Copper Alloy
Material - Plating Mating	Gold
Material - Plating Termination	Tin
Material - Resin	High Temperature Thermoplastic
Net Weight	9.320/g
Orientation	Coplanar
Packaging Type	Tray
PCB Locator	No
PCB Thickness - Recommended	2.79mm
Pitch - Mating Interface	0.75mm
Pitch - Termination Interface	0.75mm
Plating min - Mating	0.762μm
Plating min - Termination	0.762μm
Polarized to Mating Part	Yes
(p)ower-(s)ignal Configuration	68s - 0p
Temperature Range - Operating	-40° to +85°C
Termination Interface Style	Through Hole - Compliant Pin

**Solder Process Data**

Lead-Free Process Capability	N/A
------------------------------	-----

---

**Application Tooling**

---