

Features

- ☒ Frequency range : 1MHz to 170MHz
- ☒ SMD seam sealing ceramic package
- ☒ Supply voltage : 1.8V ~ 3.3V
- ☒ CMOS output
- ☒ Tri-state function available
- ☒ External dimensions (mm)
L : 5.0 x W : 3.2 x H : 1.2
- ☒ RoHS compliant & Pb free

Applications

- ☒ Networking, Server, Storage
- ☒ Wireless communications
- ☒ Fibre channel, Ethernet, SATA, SAS, PCI-E, USB, WLAN, xDSL, xPON
- ☒ PC mainboard, Notebook, HDD, SSD, Graphics card, Computer peripherals
- ☒ Audio, Video, Gaming, Printer, DSC, IP CAM, Consumer products


Electrical Characteristics

Item	7C	Conditions
Frequency Range (F_0)	1MHz ~ 170MHz	
Frequency Stability (F_{stab})	± 50 , ± 25 ppm	-10°C ~ +70°C; Note [1]
	± 50 , ± 30 , ± 25 , ± 15 ppm	-40°C ~ +85°C; Note [1]
Operating Temperature Range (T_{OTR})	-10°C ~ +70°C	
	-40°C ~ +85°C	
Supply Voltage (V_{DD})	1.8V, 2.5V, 2.8V, 3.3V	$V_{DD} \pm 10\%$
Current Consumption (I_{DD})	10 mA Max.	1MHz ~ 75MHz
	20 mA Max.	75MHz ~ 170MHz
Output Type	CMOS	
Output Load (C_L)	15 pF	
Output Voltage High (V_{OH})	90% V_{DD} Min.	
Output Voltage Low (V_{OL})	10% V_{DD} Max.	
Rise & Fall Time (T_r / T_f)	8 ns Max.	10% ~ 90% of V_{DD}
Duty Cycle	40% ~ 60%	
Start-up Time	5 ms Max.	
Enable Voltage High, Logic "1"	70% V_{DD} Min.	Input to Pin1 Note [2]
Enable Voltage Low, Logic "0"	30% V_{DD} Max.	
Phase Jitter, RMS	1 ps Max.	Note [3]
Aging (F_{aging})	± 3 ppm Max.	at 25°C ± 3 °C, first year
Storage Temperature Range (T_{STR})	-55°C ~ +125°C	

Notes:

- [1] Inclusive of frequency tolerance at 25°C, 1st year aging at 25°C, and variations over operating temperature, supply voltage, and load.
- [2] Output will be enabled if Pin1 is Logic "1" or open; Output will be disabled if Pin1 is Logic "0".
- [3] Freq. 10MHz~40MHz, integrated 12kHz~5MHz; Freq. >40MHz, integrated 12kHz~20MHz.

Dimensions



(Unit: mm)

Ordering Information

7C - 30.000M B B - T

Frequency in Hz

Please contact us for available frequencies

Packaging Method

T Tape & Reel


Supply Voltage

B	3.3 V
E	2.8 V
C	2.5 V
D	1.8 V

Frequency Stability

B	± 50 ppm (-10°C ~ +70°C)
C	± 100 ppm (-10°C ~ +70°C)
F	± 100 ppm (-40°C ~ +85°C)


Packing



Reflow Profile

Solder melting point : $220^\circ\text{C} \pm 10^\circ\text{C}$, 60 sec. Min.

Peak temperature : $260^\circ\text{C} \pm 10^\circ\text{C}$, 10 sec. Min.



Mouser Electronics

Authorized Distributor

Click to View Pricing, Inventory, Delivery & Lifecycle Information:

[TXC Corporation:](#)

[7C-27.000MBB-T](#) [7C-12.000MBB-T](#) [7C-14.31818MBA-T](#) [7C-14.31818MBB-T](#) [7C-16.000MBB-T](#) [7C-20.000MBB-T](#)
[7C-24.000MBB-T](#) [7C-24.576MBB-T](#) [7C-25.000MBB-T](#) [7C-26.000MBB-T](#) [7C-28.63636MBB-T](#) [7C-33.3330MBA-T](#) [7C-](#)
[33.3330MBB-T](#) [7C-4.000MBB-T](#) [7C-40.000MBB-T](#) [7C-44.000MBB-T](#) [7C-48.000MBB-T](#) [7C-50.000MBB-T](#) [7C-](#)
[6.000MBA-T](#) [7C-6.000MBB-T](#) [7C-8.000MBB-T](#) [7C-12.000MCA-T](#) [7C-12.000MDA-T](#) [7C-12.000MDB-T](#) [7C-](#)
[14.31818MCA-T](#) [7C-14.31818MDA-T](#) [7C-14.31818MDB-T](#) [7C-16.000MCA-T](#) [7C-16.000MDA-T](#) [7C-16.000MDB-T](#)
[7C-20.000MCA-T](#) [7C-20.000MCB-T](#) [7C-20.000MDB-T](#) [7C-24.000MCA-T](#) [7C-24.000MDB-T](#) [7C-24.576MCA-T](#) [7C-](#)
[24.576MDB-T](#) [7C-25.000MCA-T](#) [7C-25.000MCB-T](#) [7C-25.000MDA-T](#) [7C-25.000MDB-T](#) [7C-26.000MCA-T](#) [7C-](#)
[26.000MCB-T](#) [7C-26.000MDB-T](#) [7C-27.000MCA-T](#) [7C-27.000MCB-T](#) [7C-27.000MDA-T](#) [7C-27.000MDB-T](#) [7C-](#)
[28.63636MCA-T](#) [7C-28.63636MDA-T](#) [7C-28.63636MDB-T](#) [7C-33.3330MCA-T](#) [7C-33.3330MDA-T](#) [7C-33.3330MDB-T](#)
[7C-4.000MCA-T](#) [7C-4.000MCB-T](#) [7C-4.000MDA-T](#) [7C-4.000MDB-T](#) [7C-40.000MCA-T](#) [7C-40.000MCB-T](#) [7C-](#)
[40.000MDB-T](#) [7C-44.000MCA-T](#) [7C-44.000MDA-T](#) [7C-44.000MDB-T](#) [7C-48.000MCA-T](#) [7C-48.000MDB-T](#) [7C-](#)
[50.000MCA-T](#) [7C-50.000MCB-T](#) [7C-50.000MDA-T](#) [7C-50.000MDB-T](#) [7C-6.000MCA-T](#) [7C-6.000MDA-T](#) [7C-](#)
[6.000MDB-T](#) [7C-8.000MCA-T](#) [7C-8.000MDA-T](#) [7C-8.000MDB-T](#) [7C-80.000MBA-T](#) [7C-12.000MCB-T](#) [7C-](#)
[14.31818MCB-T](#) [7C-150.000MBB-T](#) [7C-16.000MCB-T](#) [7C-24.000MCB-T](#) [7C-24.576MCB-T](#) [7C-28.63636MCB-T](#) [7C-](#)
[33.3330MCB-T](#) [7C-44.000MCB-T](#) [7C-48.000MCB-T](#) [7C-6.000MCB-T](#) [7C-8.000MCB-T](#) [7C-33.333MBC-T](#) [7C-](#)
[24.576MBC-T](#) [7C-12.000MBC-T](#) [7C-6.000MBC-T](#) [7C-44.000MBC-T](#) [7C-25.000MBC-T](#) [7C-20.000MBC-T](#) [7C-](#)
[48.000MBC-T](#) [7C-4.000MBC-T](#) [7C-16.000MBC-T](#) [7C-27.000MBC-T](#)